



PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	KEY1	7	RST	13	DB5
2	KEY2	8	TXD	14	DB4
3	PSB	9	RXD	15	DB3
4	VSS	10	BUSY	16	DB2
5	3.3V	11	DB7	17	DB1
6	REQ	12	DB6	18	DB0

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	N.C	7	TXD	13	N.C
2	N.C	8	TXD	14	N.C
3	VSS	9	N.C	15	VDD
4	VSS	10	N.C	16	VDD
5	N.C	11	RXD	17	N.C
6	N.C	12	RXD	18	N.C

```

1 DISPLAY TYPE      : FSTN
2 VIEWING DIRECTION: 6 O'CLOCK
3 POLARIZER        : TRANSMISSIVE
4 DRIVE METHOD       : 1/160DUTY 1/10BIAS
5 OPERATING VOLTAGE: 15.0V (FOR REFERENCE VOLTAGE)
6 LOGIC VOLTAGE     : 2.7~3.6V
7 CONTROLLER        : ST5668A
8 OPERATING TEMP     : -10° C-----+60° C
9 STORAGE TEMP       : -20° C-----+70° C
10 BACK LIGHT        : LED

```

版次 A	ZX128160M2A_v02			SHR:	PLASTIC MAT'L:CAVITY:	
				UNIT:mm	SCALE:	
	MODEL:	SHEET: 1 of 1	DRAWING BY:		DATE:2015-2-14	
	DWG. NO.	MOLD NO.	CHECK BY:		APPROVED:	
北京中显电子有限公司						